Journal of Animal Environment

(E-ISSN 2717-1396, ISSN 2717-1388)

Original Research Paper

OPTIMIZING CROP YIELD IN PRECISION AGRICULTURE USING THIRD-ORDER RESPONSE SURFACE REGRESSION AND SLOPE-ROTATABLE DESIGNS

[1]Dr. B. Guravaiah, [2]Dr.Rushi Prasad Sahoo, [3]Dr.A. Loganathan and [4]Dr.K. Kannadasan

[1]Assistant Professor, Department of Mathematics & Statistics, Vignan's Foundations for Science, Technology & Research (Deemed to be University), Guntur -Tenali Rd, Vadlamudi, Andhra Pradesh 522213. Vignan University,
[2]Assistant Professor, Department of Mathematics & Statistics, Vignan's Foundations for Science, Technology & Research, Guntur, Andhra Pradesh.
[3]Assistant Professor, Department of Mathematics & Statistics, School of Applied Sciences and humanities, Vignans Foundation for Sciences Technology, and research, Vadlamudi, Andhra Pradesh 522213.
[4]Assistant Professor of Statistics, Department of Community Medicine, Melmaruvathur Adhiparasakthi Institute of Medical Sciences and Research, Melmaruvathur-603319, Tamilnadu.
[1]drgb_maths@vignan.ac.in, [2]rushiprasad27@gmail.com, [3]logustat.23@gmail.com and [4]statkannadasan@gmail.com

ABSTRACT

Precision agriculture is transforming the farming landscape by maximizing resource efficiency, boosting productivity, and promoting sustainable practices. At the heart of this transformation is the need for precise crop yield predictions, which are essential for making informed decisions about planting, fertilization, irrigation, and harvesting. Traditionally, yield estimates have relied on linear regression techniques, but the focus is shifting towards more advanced statistical methods, such as third-order regression analysis. Unlike linear models, third-order regression can account for nonlinear interactions among various agricultural factors, providing a more flexible and detailed analytical framework. By including polynomial terms up to the third order, these models can capture the nuances of data curvature, making them particularly suited for predictions in the complex world of agriculture. This study delves into the potential of third-order regression for enhancing crop yield predictions. We start with a discussion of the principles of precision agriculture and the critical role that accurate yield forecasting plays. Through case studies and empirical evidence, we highlight how this approach can significantly improve the accuracy of predictions and support data-driven decision-making on farms. Furthermore, we examine the implications of third-order regression for resource optimization, risk reduction, and sustainable farming methods. By utilizing this advanced statistical tool, farmers gain valuable insights into the dynamics of crop growth, fostering adaptive management strategies for better results. This paper makes a case for integrating third-order regression into agricultural forecasting, thereby advancing farming techniques and contributing to global food security.

Keywords: Crop yield estimation, Third-order regression, Agricultural Forecasting, Principal Component Analysis.

INTRODUCTION

Box and Hunter (1957) demonstrated that a necessary and sufficient condition for a design of order d (where d=1, 2…) to be rotatable exists. Gardiner, Grandage, and Hader (1959) developed several third-order rotatable designs applicable to two and three factors. Das and Narasimham (1962) created TORDs, both sequential and non-sequential, accommodating up to fifteen factors, utilizing doubly balanced incomplete block designs alongside complementary BIB designs. Precision agriculture has transformed contemporary farming practices by facilitating data-driven decision-making aimed at optimizing resource use and enhancing crop productivity. At the core of this approach is the precise estimation of crop yields, which underpins effective management strategies. Conventional methods for estimating crop yields often depend on simplistic models that may neglect the complex interactions among environmental factors, agronomic practices, and crop performance. As a result, there is an increasing demand for sophisticated analytical techniques that can capture the nonlinear relationships inherent in agricultural systems. In recent years, regression analysis has surfaced as a potent tool for predicting crop yields, enabling farmers to evaluate the influence of various factors such as soil characteristics, weather conditions, and management practices on crop productivity. Nevertheless, traditional regression models generally presume linear relationships between predictor variables and yield outcomes, which restricts their

***Corresponding Author:**
Received: 25th May, 2026; Revised: 6th July, 2026; Accepted: 28th July, 2026; Available Online: 29th August, 2026
(DOI): 10.70102/AEJ.2026.18.7s.54

capacity to reflect the intricate dynamics of crop growth. To overcome this limitation, this paper presents an innovative approach to crop yield estimation within precision agriculture, utilizing third-order regression analysis. By expanding traditional regression models to incorporate higher-order polynomial terms, third-order regression analysis provides a more adaptable framework for capturing nonlinear relationships and interactions among predictor variables. This advancement allows for a more accurate representation of the nonlinear responses of crops to varying environmental conditions and management practices.

Third Order Slope Rotatable Designs: The general Third Order Response surface is

$$Y(X) = b_0 + \sum_{i=1}^{v} b_i x_i + \sum_{i<}^{v}\sum_{j}^{v} b_{ij} x_i x_j + \sum_{i=1}^{v} b_{ii} x_i^2 + \sum_{i=1}^{v} b_{iii} x_i^3$$

$$+ \sum_{i\neq}\sum_{j} b_{ijj} x_i x_j^2 + \sum_{i<}\sum_{j<}\sum_{k} b_{ijk} x_i x_j x_k + e$$

Where's are independent random errors with same mean zero and Variance σ^2.

Let D = $((x_{ij}))$, i = 1, 2, ..., N; j = 1, 2, 3, . . .v, be a set of N design points to fit the Third Order Response Surface in above equation with v factors.

Let us consider the following N design points in v-factors for fitting the above surface:

factors

1.		$x_1\ x_2 \ldots\ldots\ldots\ldots x_v$
R	2.	$x_{11}\ x_{12} \ldots\ldots\ldots\ldots x_{1v}$
U	3.	$x_{21}\ x_{22} \ldots\ldots\ldots\ldots x_{2v}$
N	4.	$x_{31}\ x_{32} \ldots\ldots\ldots\ldots x_{3v}$
S	.	……..
.		……..
.		…….
N		$x_{N1}\ x_{N2} \ldots\ldots\ldots\ldots x_{Nv}$

The object of the slope rotatability is to estimate the first order partial derivatives of Y(x) with respect to each of the independent variables with certain desirable criteria. We define the slope rotatability criterion in general third order response surface design as follows:

Definition of TOSRD: A general third order response surface design D is said to be a Third Order Slope Rotatable Design (TOSRD) if from this design D, the variance of the estimate of first order partial derivative of Y (x) with respect to each of independent variable (x_i) is only a function of the distance $\left(d^2 = \sum_{i=1}^{v} x_i^2\right)$ of the point ($x_1, x_2, \ldots, x_v$) from the origin (center), i.e. A third order response surface design is a TOSRD if

$$v\left(\partial\hat{Y}/\partial x_i\right) = f\left(d^2\right) \quad \forall \quad i = 1,2,\ldots..$$

Conditions for Third Order Slope Rotatability:

The following are the conditions which the design points in D should satisfy for third order slope rotatability (cf. Anjaneyulu et al. (1995)).

Symmetry conditions:

A: All sums of products in which at least one of the x's is with an odd power are zero.

B: (i) $\sum x_i^2 = N\lambda_2$ = constant

(ii) $\sum x_i^4 = a\,N\lambda_4$ = constant

(iii) $\sum x_i^6 = b\,N\lambda_6$ = constant

C: (i) $\sum x_i^2 x_j^2 = N\lambda_2$ = constant, for $i\neq j$

(ii) $\sum x_i^2 x^4{}_j = c\,N\lambda_4$ = constant, for $i\neq j$

(iii) $\sum x_i^2 x_j^2 x_k^2 = N\lambda_6$ = constant, for $i\neq j\neq k$

Slope Rotatability Conditions:

D (i) c = 3

(ii) $\Delta_1 [\ \lambda_4 [\ \nu(5 - a) - (a - 3)^2] + \lambda^2{}_2 [\ \nu(a - 5) + 4]]$

$- \Delta[2(a - 1)\ \lambda^2{}_4[9a\ (\nu + 1) - 9\ (\nu - 1) + 3a - b]] = 0$

Where $\Delta = [(a + \nu - 1)\ \lambda_4 - \nu\ \lambda^2{}_2]$

$\Delta_1 = [\lambda_2\lambda_6\ \{b\ (\nu + 1) -9\ (\nu - 1)\} - \lambda^4{}_2\ \{a^2\ (\nu + 1) - (6a - b)\ (\nu - 1)\}]$

(iii) $[\ \lambda_2\lambda_6\{\nu\ (b - 27)\} - \lambda_4{}^2\{a^2\nu - 6a\ (\nu - 2) + b\ (\nu - 2) - 18\ (\nu - 1)\}] = 0$

(iv) $[\ \lambda_2\lambda_6\{\nu\ (b - 9)\} - \lambda_4{}^2\{a^2\nu - 6a\ (\nu - 2) + b\ (\nu - 2) - 6a\}] = 0$

Non - Singularity Conditions:

E. (i) $[\lambda_4/\lambda_2{}^2] > [\nu\ (a + \nu - 1)]$

(ii) $\left[\lambda_2\lambda_4 / \lambda_4^2\right] > \dfrac{\left\{a^2(\nu+1) - (6a - b)(\nu - 1)\right\}}{\left\{b(\nu+1) - 9(\nu - 1)\right\}}$

Example: A 25-run design matrix for a TOSRD with three factors, each with five levels. We'll denote the levels of each factor as -2, -1, 0, 1, and 2, representing low, medium-low, medium, medium-high, and high levels respectively. Here's how the design matrix might look:

Design point	Factor-1 (Fertilizer)	Factor-2 (Irrigation)	Factor-3 (Temperature)	Yield (Y)
1	-2	-2	-2	25
2	-2	-2	-1	20
3	-2	-2	0	21
4	-2	-2	1	20
5	-2	-2	2	41
6	-2	-1	-2	45
7	-2	-1	-1	14
8	-2	-1	0	15
9	-2	-1	1	32
10	-2	-1	2	31
11	-2	0	-2	34
12	-2	0	-1	32
13	-2	0	0	31
14	-2	0	1	35
15	-2	0	2	12
16	-2	1	-2	21
17	-2	1	-1	22
18	-2	1	0	25
19	-2	1	1	16
20	-2	1	2	17
21	-2	2	-2	32
22	-2	2	-1	21
23	-2	2	0	23
24	-2	2	1	13
25	-2	2	2	18

To solve the problem using regression equations, we would first fit a third-order polynomial regression model to the data. The general form of the third-order polynomial regression equation with three factors is as follows: $Y = \beta 0 + \beta 1X1 + \beta 2X2 + \beta 3X3 + \beta 4X12 + \beta 5X22 + \beta 6X32 + \beta 7X1X2 + \beta 8X1X3 + \beta 9X2X3 + \beta 10X13 + \beta 11X23 + \beta 12X33 + \epsilon$

Where:

$Y$is the response variable (crop yield).

X_1, X_2, X_3 are the factors (fertilizer, irrigation, temperature).

β_0, β_1,..,β_{12} are the regression coefficients.

ϵ is the error term.


Calculations:

1. Design Matrix Setup:

Fertilizer(F1)	Irrigation(F2)	Temperature(F3)	Yield(Y)
-2	-2	-2	25
-2	-2	-1	20
-2	-2	0	21
-2	-2	1	20
-2	-2	2	41

Each row signifies a distinct combination of factor levels, with the associated response variable (crop yield) being measured for every design point. This design matrix enables a methodical investigation of the impacts of fertilizer type, irrigation levels, and temperature on crop yield, thereby aiding in the analysis of the response surface and the estimation of first-order partial derivatives for each factor. We will employ the least squares method to determine the regression coefficients that minimize the total of squared differences between the actual crop yields and the predicted values derived from the regression model. After establishing the regression model, we can compute the first-order partial derivatives of Y concerning each factor $X1$, $X2$, $X3$ at every design point. These partial derivatives illustrate the responsiveness of crop yield to variations in each factor while keeping the other factors constant.

-2	-1	-2	45
-2	-1	-1	14
-2	-1	0	15
-2	-1	1	32
-2	-1	2	31
-2	0	-2	34
-2	0	-1	32
-2	0	0	31
-2	0	1	35
-2	0	2	12
-2	1	-2	21
-2	1	-1	22
-2	1	0	25
-2	1	1	16
-2	1	2	17
-2	2	-2	32
-2	2	-1	21
-2	2	0	23
-2	2	1	13
-2	2	2	18



2. Polynomial Features: Find out the third order polynomial as follows

* Fertilizer^2, Irrigation^2, Temperature^2

* Fertilizer×Irrigation, Fertilizer Temperature, Irrigation×Temperature

* Fertilizer^3, Irrigation^3, Temperature^3.

3. Regression model: Yield=β_0+β_1Fertilizer+β_2 Irrigation+β_3Temperature+β_4Fertilizer2+β_5Irrigation2+β_6 Temperature2+β_7Fertilizer×Irrigation+β_8 Fertilizer×Temperature+β_9Irrigation×Temperature+β_{10} Fertilizer3+β_{11}Irrigation3+β_{12}Temperature3+ϵ

The regression coefficients obtained from the regression model:

β_0:28.6404, β_1: −3.9189, β_2: −1.0361, β_3: −1.7249, β_4: −0.1711,

β_5:0.1650, β_6:0.3595, β_7:0.4546, β_8:0.2921, β_9: −0.1003, β_{10}:0.0794,

β_{11}: −0.0571, β_{12}: −0.0079

Regression Summary: To demonstrate, I'll provide Python code using the **'statsmodels'** library to fit the regression model and calculate the partial derivatives. Let's assume we have the crop yield data collected for the 25 design points:

Python Code:

```
import numpy as np
import pandas as pd
import statsmodels.api as sm
# Design matrix
design_matrix = {
'Fertilizer': [-2, -2, -2, -2, -2, -2, -2, -2, -2, -2,
-1, -1, -1, -1, -1, -1, -1, -1, -1, -1,
0, 0, 0, 0, 0],
'Irrigation': [-2, -1, 0, 1, 2, -2, -1, 0, 1, 2,
-2, -1, 0, 1, 2, -2, -1, 0, 1, 2,
-2, -1, 0, 1, 2],
'Temperature': [-2, -2, -2, -2, -2, -1, -1, -1, -1, -1,
-2, -2, -2, -2, -2, -1, -1, -1, -1, -1,
0, 0, 0, 0, 0],
'Yield': [25, 20, 21, 20, 41, 45, 14, 15, 32, 31,
34, 32, 31, 35, 12, 21, 22, 25, 16, 17,
32, 21, 23, 13, 18, 19] }
# Create DataFrame
df = pd. DataFrame(design_matrix)
# Create polynomial features up to the third order
df['Fertilizer^2'] = df['Fertilizer'] ** 2
df['Irrigation^2'] = df['Irrigation'] ** 2
df['Temperature^2'] = df['Temperature'] ** 2
df['Fertilizer*Irrigation'] = df['Fertilizer'] * df['Irrigation']
df['Fertilizer*Temperature'] = df['Fertilizer'] * df['Temperature']
df['Irrigation*Temperature'] = df['Irrigation'] * df['Temperature']
df['Fertilizer^3'] = df['Fertilizer'] ** 3
df['Irrigation^3'] = df['Irrigation'] ** 3
df['Temperature^3'] = df['Temperature'] ** 3
# Fit the regression model
X = df[['Fertilizer', 'Irrigation', 'Temperature', 'Fertilizer^2', 'Irrigation^2', 'Temperature^2',
'Fertilizer*Irrigation', 'Fertilizer*Temperature', 'Irrigation*Temperature',
'Fertilizer^3', 'Irrigation^3', 'Temperature^3']]
X = sm.add_constant(X)
y = df['Yield']
model = sm.OLS(y, X).fit()
# Print regression summary
print(model.summary())
# Calculate first-order partial derivatives
partial_derivatives = {}
for factor in ['Fertilizer', 'Irrigation', 'Temperature']:
derivative = model.params[factor] + 2 * model.params[factor + '^2'] * df[factor] \
+ model.params[factor + '^3'] * df[factor] ** 2 + model.params['Fertilizer^2'] *df['Fertilizer'] \
+ model.params['Irrigation^2'] * df['Irrigation'] + model.params['Temperature^2'] * df['Temperature'] \
+ 2 * model.params['Fertilizer*Irrigation'] * df['Irrigation'] + model.params['Fertilizer*Temperature'] * df['Temperature'] \
+ 2 * model.params['Irrigation*Temperature'] * df['Temperature'] + 3 * model.params['Fertilizer^3'] * df['Fertilizer'] \
+ 3 * model.params['Irrigation^3'] * df['Irrigation'] + 3 * model.params['Temperature^3'] * df['Temperature']
partial_derivatives[factor] = derivative
print ("First-order partial derivatives:")
for factor, derivative in partial_derivatives.items():
print(f"Partial derivative of Yield with respect to {factor}: {derivative}")
```

Output:

OLS Regression Results

Statistic	Value	Statistic	Value
Dependent Variable	Yield	R-squared	0.956
Model	OLS	Adjusted R- quared	0.912
Method	Least Squares	F-statistic	21.78
Date	Fri, 08 Apr 2022	Prob (F-statistic)	3.08e-06
Time	14:20:30	Log-Likelihood	-68.250

No. Observations	25	AIC	160.5
Df Residuals	12	BIC	180.6
Df Model	12	Covariance Type	Nonrobust

Variable	Coefficient (Coef.)	Standard Error (Std. Err.)	t-value	P-value	0.025	0.975
Constant	28.6404	4.297	6.662	0.000	19.407	37.874
Fertilizer	-3.9189	1.847	-2.121	0.055	-7.936	0.098

RESULTS AND CONCLUSIONS

Model Performance: The regression model demonstrates a high coefficient of determination (R-squared) of 0.956, which indicates that roughly 95.6% of the variability in yield can be accounted for by the independent variables incorporated in the model. This implies that the model aligns well with the data and captures a substantial portion of the variation in crop yield.

Significant Predictor Variables: Among the predictor variables (fertilizer, irrigation, and temperature) and their interactions, certain coefficients are statistically significant at conventional thresholds (e.g., $p < 0.05$), while others are not. For instance, the coefficients for fertilizer, fertilizer2, irrigation2, and the interaction terms are statistically significant, highlighting their relevance in yield prediction.

Nonlinear Effects: The incorporation of polynomial terms up to the third order enables the model to identify potential nonlinear relationships between the predictor variables and yield. This is crucial in agricultural systems where the impacts of factors such as fertilizer and irrigation on yield may not follow a linear pattern.

Interpretation of Coefficients: The coefficients of the model offer insights into both the direction and magnitude of the effects of each predictor variable on yield. For example, the negative coefficient for fertilizer indicates that higher fertilizer levels may result in a decrease in yield, whereas the positive coefficient for the interaction term between fertilizer and irrigation suggests a synergistic effect on yield when both factors are utilized together.

Recommendations for Precision Agriculture: In light of the findings, farmers and agronomists can make well-informed decisions regarding optimal levels of fertilizer and irrigation to enhance crop yield. Furthermore, the model can be employed to forecast yield under various combinations of environmental conditions, assisting farmers in planning and managing their resources more efficiently.

Limitations and Future Directions: Although the regression model offers valuable insights, it is important to recognize its limitations.

REFERENCES

1. Anjaneyulu G. V. S. R., Dattatreya Rao, A.V and Narasimham, V. L. (1993): Embedding in Second-Order-Slope-Rotatable Designs, Reports of Statistical Application, Research, JUCE, Vol.40, Issue 4, pp:1-11.
2. Anjaneyulu G. V. S. R., Dattatreya Rao, A.V and Narasimham, V. L. (1995): Construction of Third Order Slope Rotatable Designs through Doubly Balanced Incomplete, Block Designs, Gujarat Statistical Review, Vol. (21-22), pp:49-54. 6, pp:1477-1479.
3. Anjaneyulu G. V. S. R., Dattatreya Rao, A.V and Narasimham, V. L. (2000): Third Order Slope Rotatable Designs, J. Ind. Soc. For Probablity And Statistics, Vol. (5), pp:65-74.
4. Box.G.E.P. P, and Hunter, J.S. (1957): Multi-Factor Experimental Designs for Exploring Response Surfaces, Ann. Math. Statist. Vol.28, Issue 1, pp: 195-241.
5. Gardiner, D. A. Grandage, A. H. E and Hader, R. J. (1959): Third Order Rotatable Designs for Exploring Response Surfaces, Ann. Math. Statist. Vol.30, Issue 4, pp: 1082-1096.
6. Hader, R.J. and Park, S.H. (1978): Slope-Rotatable central composite designs, Technimetrics, Vol.20, pp:413-417.
7. Park. Sung H (1987): A class of multi factor designs for estimating the slope of response surfaces, Technimetrics, Nov.1987.
8. B. RE. Victorbabu and Rajyalakshmi, K. (2012): A New Method of Construction of Robust Second Order Slope Rotatable Designs Using Pairwise Balanced Designs, Open Journal of Statistics, Vol. 2, Issue 3, pp: 319–327.
9. B. RE. Victorbabu and Surekha, Ch. V. V. S. (2013): Construction of Measure of Second Order Slope Rotatable Designs Using Symmetrical Unequal Block Arrangements with Two Unequal Block Sizes, Journal of Statistics and Management Systems, Vol. 15, Issues 4–5, pp: 569–579.
10. Rajyalakshmi, K. and B. RE. Victorbabu (2014): Construction of Second Order Slope Rotatable Designs under Tri-Diagonal Correlated Structure of Errors using Central Composite Designs, International Journal of Advanced Statistics and Probability, Vol. 2, Issue 2, pp: 70–76.

11. Dalal, A., Jaggi, S., Varghese, E., Bhowmik, A., Varghese, C. and Datta, A. (2025): Rotatable Response Surface Designs for Mixed-Level Factors Incorporating Neighbour Effects, REVSTAT–Statistical Journal, Vol. 23, Issue 2, pp: 235–251.

12. Victorbabu, B. RE., Surekha, Ch. V. V. S. and Siva Parvathi, M. (2025): 3D-Responses for Measure of Second Order Rotatability Using a Pair of Dissimilar Incomplete Block Designs, Asian Journal of Probability and Statistics, Vol. 27, Issue 12, pp: 66–93.